

esterpeel™

heat sealable lidding films

Esterpeel PCS

A strong co-extruded polyester film designed to give weld seals. Heat seal on one side, printable surface on the other. Conforms to current Health and Safety legislation for use as a food wrapping.

Properties

Seals to:	A-PET, C-PET, itself
Gauge:	20 micron (36m ² /kg) 30 micron (24m ² /kg)
Seal conditions:	120°C - 200°C
Transmission:	20 micron: Oxygen 72cm ³ /m ² /day, WVTR 18g/m ² /day 30 micron: Oxygen 48cm ³ /m ² /day, WVTR 13g/m ² /day

Feature points

- Weld seal
- Dual Ovenable
- Frozen, chilled or ambient pack
- Available in 20 micron or 30 micron gauges
- Single ply film

Notes

- While FFP takes every precaution to ensure that lidding films are suitable for the end use specified, the responsibility for the specific application lies with the packer
- Any contamination present may result in seal failure, therefore sealing flanges should be kept clean at all times
- Esterpeel PCS may be printed with inks conforming to SBPIM regulations for inks and varnishes for non-direct food contact. Ink coverage may be limited because of ink build up
- Esterpeel PCS has been tested and complies with all current European Food Contact Regulations including microwave and conventional oven cooking